

SPDTU080100D – SFP+ Dual Fiber DWDM Tunable

DWDM Tunable 50GHz / 80 km / 10x Gigabit Ethernet

For your product safety, please read the following information carefully before any manipulation of the transceiver:



ESD

This transceiver is specified as ESD threshold 1kV for SFI pins and 2kV for all others electrical input pins, tested per MIL-STD-883G, Method 3015.4 / JESD22-A114-A (HBM). However, normal ESD precautions are still required during the handling of this module.



LASER SAFETY

This is a Class1 Laser Product according to IEC 60825-1:2007. This product complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated (June 24, 2007).

The optical ports of the module need to be terminated with an optical connector or with a dust plug in order to avoid contamination.


1. Overview

SPDTU080100D is a high performance C-band tunable transceiver module for 9.95 Gbps to 11.3 Gbps data links over a single mode fibre pair. The maximum reach is 80km¹ for a 23dB end of life (EOL) power budget. The transmitter is a cooled C-band tunable transmitter (ILMZ), the receiver is an APD photodiode.

This transceiver module is compliant with the Small Form-factor Pluggable (SFP+) Multisource Agreement (MSA) and hot pluggable. Always contact Skylane Optics® commercial agents for compatibility with different equipment platforms.

2. Features

- SFP+ Multi-Source Agreement compliant [SFF-8431] revision 4.1 and SFP DWDM Tunable SFF-8690 compliant revision 1.4
- Hot pluggable SFP+ footprint
- Serial ID functionality supported according to (SFF-8472)
- Supports Data Rates between 9.95Gbps and 11.3Gbps
- Dual LC connector
- C-band tunable (DWDM 50GHz) Laser
- 80km point-to-point transmission on single mode fibre
- Operating temperature range 0°C to 70°C
- Power dissipation (<1.65W)
- Digital Diagnostics monitoring (DDM)



3. Applications

- 10GBASE-ZR/ZW
- 10x Fiber Channel

4. Optical Interface

P/N	Wavelength [nm]	Optical Output Power [dBm]	Receiver Sensitivity [dBm]	Dispersion Penalty [dB]	Receiver Overload [dBm]	Power Budget [dB]
SPDTU080100D	ITU DWDM 50GHz	-1 to 3	-24	2	-7	≥ 23

1. Distance is estimated assuming typical optical losses after decent quality fibre deployment; Only optical budget value is guaranteed.

2. EOL, over operating temperature range

3. Measured at 10.3125Gbps, PRBS 231-1, BER≤10⁻¹²

4. The optical input to the receiver should not exceed this value. Transmitters must never be directly connected to receivers (optical loop back) before ensuring that proper optical attenuation is used

5. Technical Parameters

5.1. Recommended Operating Conditions

Parameter	Min	Typ	Max	Unit	Notes
Storage temperature	-40		85	°C	
Operating Case Temperature	0		70	°C	
Relative Humidity	5		95	%	Non condensing
Power Supply Voltage	3.135		3.465	V	
Power Supply Current			500	mA	
Power Consumption			1.65	W	

5.2. Transmitter Optical Specifications

Parameter	Min	Typ	Max	Unit	Notes
Optical Output Power	-1		3	dBm	5
Centre Wavelength Range	1528.38		1568.77	nm	
Centre Wavelength	$\lambda_c - 20$	λ_c	$\lambda_c + 20$	pm	6
Spectral Width (-20dB)			200	pm	
Extinction ratio	9			dB	
Dispersion Penalty			2	dB	

5. Output power coupled into a 9/125 μm single-mode fibre

6. TU-T G.694.1 50GHz DWDM. For available wavelengths, see section 9

5.3. Receiver Optical Specifications

Parameter	Min	Typ	Max	Unit	Notes
Receiver Sensitivity			-24	dBm	7
Receiver Overload	-7			dBm	7
Receiver Operating Range	1528.38		1568.77	nm	

7. Measured at $\leq 10.5\text{Gbps}$, PRBS 2³¹-1, ER=9dB, BER $\leq 10^{-12}$

6. Transceiver Electrical Pad Layout




Figure 2. Transceiver Electrical Pad Layout

7. Module Electrical Pin Definition

SFP+ MSA (SFF-8431)

Pin Number	Name	Function
1	VeeT	Module Transmitter Ground
2	Tx_Fault	Module Transmitter Fault
3	Tx_Disable	Transmitter Disable
4	SDA	2-Wire Serial Interface Data
5	SCL	2-Wire Serial Interface Clock
6	Mod_ABS	Module Absent
7	RS0	Not Used
8	Rx_LOS	Receiver Loss of Signal
9	RS1	Not Used
10	VeeR	Module Receiver Ground
11	VeeR	Module Receiver Ground
12	RD-	Receiver Inverted Data Output
13	RD+	Receiver Non-Inverted Data Output
14	VeeR	Module Receiver Ground
15	VccR	Module Receiver 3.3V Supply
16	VccT	Module Transmitter 3.3V Supply
17	VeeT	Module Transmitter Ground
18	TD+	Transmitter Non-Inverted Data Input
19	TD-	Transmitter Inverted Data Input
20	VeeT	Module Transmitter Ground

8. EEPROM

SFP+ MSA (SFF-8472)




Figure 3. EEPROM of a SFP+

Datasheet

SPDTU080100D.docx



9. Ordering Information

Part Number	Description
SPDTU080100D	SFP+ DWDM dual fiber, Tx (C-band tunable), Rx (APD), 80km, power budget 23dB, 9.95 Gbps up to 11.3 Gbps, LC connector, 1.65W, 0°C to 70°C, DDM

10. Document Revision Information

Revision	Description
A	Initial release

Skylane Optics supplies a broad range of optical transceivers. Our engineers work closely with our customers to find the best solutions for every application. We are committed to provide high quality products and services to our customers.

For questions on this product please contact:
support@skylaneoptics.com

Beyond Quality

Reliable Alliance

Performing Smartly